# Data sheet – profile for pool copings "Frontlight"






### **Product description**


The TALUX pool coping profile Frontlight makes it quick and easy to build high-quality pool copings with integrated indirect lighting. The visible part of the profile that protrudes over the edge of the pool is the visual finish of the TALUX system on the pool and can be powder-coated in a RAL colour of your choice. Use the light channel on the front the profile to illuminate the pool impressively and set the stage.

The pool coping profile Frontlight is compatible with the TALUX Slim system (22 mm) and complements the functional advantages of the TALUX System with innovative and creative options for pool coping and indirect lighting.

To match the profile, we offer ready-made corner modules, water-protected (IP67) LED strips in various colours and white hues, control sets, and clip-on plastic covers for light diffusion. To achieve a premium quality surface, the profiles are also available powder-coated in a RAL colour of your choice.

#### Technical data





# The advantages at a glance

- ✓ Integrated light channel for straightforward installation of indirect lighting
- ✓ Innovative system solution
- Low profile height of 44 mm for low build-up heights
- ✓ Suitable for tiles with 20 mm thickness
- Profiles & LED technology from a single source

# Technical data for profiles

Material: Aluminium EN AW 6060 T 66 Surface: mill-finished / powder-coated Lengths: 3 m / 6 m

#### System accessories

- Exterior and interior corners
- Plastic covers
- LED lighting and controls

#### LED lighting (IP67)

- Warm white / neutral white / cool white
- CCT (all shades of white)
- RGBWW (all colours + warm white)
- RGB-CCT (all colours + all shades of white)

# LED control

- Switch
- Remote control
- App control (WiFi)
- DALI